PRECONDITIONING CELL-CENTERED FINITE DIFFERENCE EQUATIONS ON GRIDS WITH LOCAL REFINEMENT

ILYA. D. MISHEV

ABSTRACT. We consider cell-centered finite difference discretizations with local refinement for nonsymmetric boundary value problems. Preconditioners with mesh independent convergence properties for corresponding matrices are constructed. The method is illustrated with numerical experiments.

1. INTRODUCTION

This paper is devoted to construction of preconditioners of Bramble-Ewing-Pasciak-Schatz (**BEPS**) type [3] for solving nonsymmetric boundary value problems discretized by finite difference schemes on cell-centered grids with local refinement. Approximation properties of cell-centered finite difference schemes are investigated in [5], [11] for the symmetric problems, and in [7] for the nonsymmetric ones (see also [4] and [9]). The theory for two-level preconditioners is developed in [3],[6] and [8]. We extend the results obtained in [6] for nonsymmetric matrices without loss of optimality of the preconditioners, i.e., convergence rate is mesh independent.

We consider the following convection-diffusion boundary value problem: find a function u(x) which satisfies the following differential equation and boundary condition:

(1.1)
$$\begin{cases} \operatorname{div}(-a(x)\nabla u(x) + \underline{b}(x)u(x)) &= f(x) & \text{in } \Omega \\ u(x) &= 0 & \text{on } \Gamma \end{cases}$$

where $\Omega \subset \mathbb{R}^2$ is a bounded domain and $\Gamma = \partial \Omega$. The coefficients a(x) and $\underline{b}(x) = (b_1(x), b_2(x))$ are supposed to fulfill for some constants a_0 and β_0 , β_1 the conditions

(i) $a(x) \ge a_0 > 0, \ a(x) \in W^1_{\infty}(\Omega),$

 $(ii) \mid b_i(x) \mid \leq \beta_1, \ b_i \in W^1_{\infty}(\Omega),$

and in order to obtain coercivity it is sufficient that

 $(iii) \ (\nabla \underline{b}(x)) \ge \beta_0 > 0 \,.$

The function f(x) is given in Ω and $f(x) \in L^2(\Omega)$.

¹⁹⁹¹ Mathematics Subject Classification. 65N22, 65F10.

Key words and phrases. Cell-centered finite differences, nonsymmetric elliptic problem, local refinement, optimal preconditioners.

This paper is in final form and and no version of it will be submitted for publication elsewhere.

ILYA. D. MISHEV

2. Description of the preconditioners

Suppose the domain Ω is divided in two parts Ω_1 and Ω_2 , $\Omega = \Omega_1 \cup \Omega_2$, $\Omega_1^o \cap \Omega_2^o = \phi$, where Ω_1 is the nonrefined and Ω_2 is the refined subdomain. Let us consider the composite grid ω (see [7] for a detailed description) divided in the same way, i.e., $\omega = \omega_1 \cup \omega_2$, $\omega_1 \subset \Omega_1$, $\omega_2 \subset \Omega_2$. The nodes of ω can be partitioned into three groups. The first group consists of the nodes in the refined subdomain Ω_2 , the second one consists of nodes in Ω_1 next to the interface boundary, denoted by γ , and in the last are the rest of the nodes from Ω_1 . Correspondingly our finite difference matrix A [7] admits a three-by-three block structure, i.e., we have

$$A = \begin{bmatrix} A_{11} & A_{12} & 0 \\ A_{21} & A_{22} & A_{23} \\ 0 & A_{32} & A_{33} \end{bmatrix} \begin{cases} \lambda \omega_2 \\ \beta \gamma \\ \lambda \omega_1 \setminus \gamma \end{cases}$$

We need also the s.p.d. coarse-grid matrix \tilde{C} , which is a approximation of matrix \tilde{A} derived from the nonrefined finite difference scheme. We partition \tilde{C} in the same manner as A into a three by three block structure on the nonrefined mesh $\tilde{\omega}$

$$\tilde{C} = \begin{bmatrix} \tilde{C}_{11} & \tilde{C}_{12} & 0\\ \tilde{C}_{21} & \tilde{C}_{22} & \tilde{C}_{23}\\ 0 & \tilde{C}_{32} & \tilde{C}_{33} \end{bmatrix} \begin{cases} \tilde{\omega}_2\\ \tilde{\gamma}\\ \tilde{\omega}_1 \setminus \gamma \end{cases},$$

where $\tilde{\omega}_2 = \tilde{\omega} \cap \Omega_2$. Then the preconditioner (**BEPS**) is constructed as follows [3], [6].

Given a vector $v = [v_1 \ v_2 \ v_3]^T$, we perform the following steps (i) solve in Ω_2

$$A_{11}y_1^F = v_1;$$

(ii) compute the defect

$$d = v - A \begin{bmatrix} y_1^F \\ 0 \\ 0 \end{bmatrix} = \begin{bmatrix} 0 \\ v_2 - A_{21}y_1^F \\ v_3 \end{bmatrix} \overset{\}\omega_2}{};$$

(*iii*) approximate the coarse-grid correction

$$\tilde{C}\tilde{y} = \begin{bmatrix} 0\\ v_2 - A_{21}y_1^F\\ v_3 \end{bmatrix} \tilde{\omega}_2 ;$$

(iv) find y_1^H in ω_2 such that

$$A_{11}y_1^H + A_{12}\tilde{y}_2 = 0.$$

Then

$$y = B^{-1}v = \begin{bmatrix} y_1^F + y_1^H \\ \tilde{y}_2 \\ \tilde{y}_3 \end{bmatrix}.$$

In matrix notation

$$B = \begin{bmatrix} A_{11} & 0 \\ A_{21} \\ 0 \end{bmatrix} \tilde{S}_{c} \begin{bmatrix} I & [A_{11}^{-1}A_{12} & 0] \\ 0 & I \end{bmatrix},$$

where

$$\tilde{S}_{c} = \begin{bmatrix} \tilde{A}_{22}^{c} - \tilde{A}_{21}^{c} \tilde{A}_{11}^{c^{(-1)}} \tilde{A}_{12}^{c} & \tilde{A}_{23}^{c} \\ \tilde{A}_{32}^{c} & \tilde{A}_{33}^{c} \end{bmatrix}$$

is the Schur complement of the coarse-grid matrix \tilde{C} .

Using the results in [7], we can easily prove the following auxiliary result.

Lemma 2.0.1. There exists two positive constants $\hat{\gamma}_1$ and $\hat{\gamma}_2$ independent of h such that

$$\hat{\gamma}_1 v_2^T A v_2 \le v^T A v$$
$$v^T A y \le \hat{\gamma}_2 (v_2^T \tilde{A} v_2)^{\frac{1}{2}} (y_2^T \tilde{A} y_2)^{\frac{1}{2}}$$

where $v = \left[\begin{array}{c} v_1 \\ v_2 \end{array} \right] \begin{array}{c} \} \omega \backslash \tilde{\omega} \\ \} \omega \end{array} .$

Our task is to estimate the eigenvalues of the preconditioned matrix $B^{-1}A$. We have

$$B^{-1}A = \left[\begin{array}{cc} I & * \\ 0 & (\tilde{S}_c)^{-1}S_2 \end{array} \right]$$

and from

$$\lambda(B^{-1}A) = (1, \lambda((\tilde{S}_c)^{-1}S_2))$$

is clear that we have to evaluate the spectrum of $((\tilde{S}_c)^{-1}S_2)$.

We consider two cases for the matrices C and \tilde{C} , respectively:

1. $\tilde{C} = \frac{\tilde{A} + \tilde{A}^T}{2}$, $C = \frac{A + A^T}{2}$, i.e., the symmetric part of \tilde{A} and A, and 2. $\tilde{C} = \tilde{A}^{(1)}$, $C = A^{(1)}$,

i.e., the part arising from the approximation of the diffusion term.

For the first case we have $v^T \tilde{A} v = v^T \tilde{C} v$. Using the results in [7], we get for the second one

$$v_2^T \tilde{A}^{(1)} v_2 \le v_2^T \tilde{A} v_2 \le E v_2^T \tilde{A}^{(1)} v_2$$

Therefore, there exist constants γ_1 and γ_2 such that the following inequalities hold:

(2.2)
$$\gamma_1 v_2^T \tilde{C} v_2 \le v^T A v$$

(2.3)
$$v^T A y \le \gamma_2 (v_2^T \tilde{C} v_2)^{\frac{1}{2}} (y_2^T \tilde{C} y_2)^{\frac{1}{2}}.$$

We apply the technique proposed by Vassilevski [10] for the same problem and prove the auxiliary result.

Lemma 2.0.2. Let the assumptions (2.2) and (2.3) be fulfilled. Then the following spectral equivalence relations hold:

(2.4)
$$\gamma_1 v_2^{(2)^T} \tilde{S}_c v_2^{(2)} \le v_2^{(2)^T} S_2 v_2^{(2)} \text{ for all } v_2^{(2)},$$

$$w_2^{(2)^T} S_2 v_2^{(2)} \le \frac{\gamma_2^2}{\gamma_1} (w_2^{(2)^T} \tilde{S}_c w_2^{(2)^T})^{\frac{1}{2}} (v_2^{(2)^T} \tilde{S}_c v_2^{(2)^T})^{\frac{1}{2}} \text{ for all } w_2^{(2)} \text{ and } v_2^{(2)}$$

Now we are ready to prove our main result.

Theorem 2.0.1. The spectrum of $B^{-1}A$ lies in the following rectangle

 $\{z \, : \, \operatorname{Re} z \geq \min\left(1, \gamma_{1}\right), \quad \operatorname{Re} z \, , \, |\operatorname{Im} z| \leq \max\left(1, \gamma_{2}^{2} / \gamma_{1}\right)\}$

Proof. We can rewrite (2.4) in the following way

$$\frac{v_2^{(2)^T} S_2 v_2^{(2)}}{v_2^{(2)^T} \tilde{S}_c v_2^{(2)}} = \frac{v_2^{(2)^T} \frac{1}{2} \left(S_2^T + S_2\right) v_2^{(2)}}{v_2^{(2)^T} \tilde{S}_c v_2^{(2)}} \ge \gamma_1 \ .$$

Hence

$$\begin{aligned} \operatorname{Re} \lambda[B^{-1}A] &\geq \min\left(1, \operatorname{Re} \lambda\left[\tilde{S}_{c}^{-1}S_{2}\right]\right) \\ &\geq \min\left(1, \lambda\left[\tilde{S}_{c}^{-\frac{1}{2}}\frac{1}{2}\left(S_{2}^{T}+S_{2}\right)\tilde{S}_{c}^{-1\frac{1}{2}}\right]\right) \\ &\geq \min\left(1, \gamma_{1}\right). \end{aligned}$$

For the other bound we have

$$|\lambda[B^{-1}A]| \le \max\left(1, \left|\lambda\left[\tilde{S}_{c}^{-1}S_{2}\right]\right|\right)$$

 and

$$\frac{v_2^{(2)^T} S_2 v_2^{(2)}}{v_2^{(2)^T} \tilde{S}_c v_2^{(2)}} \le \frac{\gamma_2^2}{\gamma_1}$$

Then

$$\left|\lambda\left[\tilde{S}_{c}^{-1}S_{2}\right]\right| = \left|\lambda\left[\tilde{S}_{c}^{-\frac{1}{2}}S_{2}\tilde{S}_{c}^{-\frac{1}{2}}\right]\right| \le \frac{\gamma_{2}^{2}}{\gamma_{1}}$$

Theorem 2.1 implies the following corollary.

Corollary 2.0.1. The the preconditioned GCG-LS from Axelsson [1], [2] for solving the composite grid system with the preconditioner B will have rate of convergence independent of h and jumps of the coefficient a(x).

3. NUMERICAL RESULTS

In this section we illustrate the convergence behavior of the two preconditioners on two model examples. We solve the problem (1.1) in the domain $\Omega = (0, 1) \times (0, 1)$ with the velocity field

(3.5)
$$b_1 = (1 + x \cos(\alpha)) \cos(\alpha), \quad b_2 = (1 + y \sin(\alpha)) \sin(\alpha),$$

where $\alpha = 15^{\circ}$. The refined subdomain is $\Omega_2 = \{0.5 \le x_1 \le 1, 0.5 \le x_2 \le 1\}$

Problem 1. Consider a smooth solution u(x) and a smooth coefficient a(x),

$$a(x) = \left[1 + 10(x_1^2 + x_2^2)\right]^{-1}, \quad u(x) = \phi_1(x_1)\psi_2(x_2)$$

$$\phi_i(x_i) = \begin{cases} \sin^2\left(\pi \frac{x_i - d_i}{1 - d_i}\right), & x_i \in (0.875, 1), \\ 0, & otherwise. \end{cases}$$

,

		Problem 1		Problem 2	
n_c	h_c/h_f	iter	arfac	iter	arfac
	3	4	0.0264	3	0.0038
20	5	3	0.0098	3	0.0038
	7	4	0.0229	3	0.0036
	3	3	0.0070	3	0.0032
40	5	3	0.0055	3	0.0030
	7	2	0.0009	3	0.0029
80	3	2	0.0006	2	0.0009
	5	1	0.0001	2	0.0008

TABLE 1. Preconditioner with $\tilde{C} = (\tilde{A} + \tilde{A}^T)/2$

TABLE 2. Preconditioner with $\tilde{C} = \tilde{A}^{(1)}$

		Problem 1		Problem 2	
n_c	h_c/h_f	iter	arfac	iter	arfac
	3	4	0.0203	3	0.0038
20	5	3	0.0093	3	0.0038
	7	3	0.0082	3	0.0037
	3	2	0.0009	3	0.0032
40	5	2	0.0006	3	0.0030
	7	2	0.0005	3	0.0029
80	3	2	0.0004	2	0.0010
	5	1	0.0001	2	0.0008

We report the numbers of iterations for the preconditioned **GCG-LS** [1], [2]. The stopping criterion is $||r_{last}||/||r_{first}|| < 10^{-6}$, r = b - Ay where y is the current iteration, and $arfac = (||r_{last}||/||r_{first}||)^{1/iter}$. Our initial guess is found by constant interpolation of a coarse grid solution.

Problem 2. Consider a piecewise continuous solution u(x) and piecewise constant coefficient a(x):

$$u(x) = \left[\frac{(x_1 - b_1)(x_2 - b_2)}{a(x)}\right]\phi(x),$$

where

$$\phi(x) = \sin\left(\frac{\pi}{2}x_1\right) \sin\left(\frac{\pi}{2}x_2\right), \quad a(x) = \begin{cases} 1000, & x_i > (n_c + 3)h_c/2, \\ 1, & otherwise. \end{cases}$$

The results in Tables 1 and 2 show that the convergence rate of the considered algorithms is independent of a mesh size h, jumps of the coefficient a(x) and smoothness of the solution. Although each iteration is relatively expensive (it includes solution of two problems on a refined grid and one problem on a coarse grid), the overall algorithm is very efficient because we need only a few iteration.

The theoretical and numerical results are in accordance with the general theory of overlapping domain decomposition. In fact we have overlap of the whole refined subdomain and that explanes the very good numerical results we report.

ILYA. D. MISHEV

4. Acknowledgments

The author would like to thank Dr. P. S. Vassilevski for the helpful discussions and constant encouragement which make this paper possible. This work was partially supported by funding from DOE, DE-AC05-840R21400, Martin Marietta, Subcontract, SK965C and SK966V. The author is also grateful to the organizing committee of the Seventh International Conference on Domain Decomposition in Scientific and Engineering Computing for the help to attend the conference.

References

- O. Axelsson, A generalized conjugate gradient, least square method, Numer. Math. 51 (1987), 209–227.
- O. Axelsson, A restarted version of a generalized preconditioned conjugate gradient method, Comm. Appl. Numer. Methods 4 (1988), 521-530.
- J. H. Bramble, R. E. Ewing, J. E. Pasciak, A. H. Schatz, Preconditioning technique for the efficient solution of problems with local grid refinement, Comp. Meth. Applied Mechanics and Eng. 67 (1988), 149-159.
- Z. Cai, J. Mandel, S. McCormick, The finite volume element method for diffusion equations on composite grids, SIAM J.Numer. Anal. 28 (1991), 392-402.
- R. E. Ewing, R. D. Lazarov, P. S. Vassilevski, Local refinement techniques for elliptic problems on cell-centered grids. I: Error analysis Math. Comp. 56 (1991), 437-461.
- R. E. Ewing, R. D. Lazarov, P. S. Vassilevski, Local refinement techniques for elliptic problems on cell-centered grids.II: Two-grids iterative methods, J. on Numer. Linear Algebra 56 (1991), 437-461.
- 7. R. D. Lazarov, I. D. Mishev, P. S. Vassilevski, *Finite Volume Methods with Local Refinement Convection-Diffusion Problems*, Computing (to appear).
- J. Mandel, S. McCormick, Iterative solution of elliptic equations with refinement: The twolevel case, Domain Decomposition Methods (T.F. Chan, R. Glovinski, J. Periaux, and O.B. Widlund, eds.), "SIAM", Philadelphia, 1989.
- 9. S. McCormic, Multilevel Adaptive Methods for Partial Differential equations, "SIAM", 1988.
- P. S. Vassilevski, Preconditioning nonsymmetric and indefinite finite element matrices, J. Numer. Linear Algebra Appl. 1 (1992), 59-76.
- P. S. Vassilevski, S. I. Petrova, R. D. Lazarov, Finite difference schemes on triangular cellcentered grids with local refinement, SIAM J. Sci. Stat. Comput. 13 (1992), 1287–1313.

Department of Mathematics, and Institute for Scientific Computation, Texas A & M University, College Station, TX 77843-3368

E-mail address: mishev@math.tamu.edu